



MODEL NUMBER
W-M3000

Photoelectric Smoke Alarm 240V Interconnected

KEY FEATURES



- ✓ Photoelectric Smoke Detection
- ✓ 240V Mains Powered with Battery Backup
- ✓ Wired & Wireless Interconnection
- ✓ Hush Function
- ✓ Auto Pairing

Power & Electrical

- › Power Supply: AC Mains
- › Rated Voltage: 220–240Vac, 50Hz
- › Backup Battery: 9V Lithium (Replaceable)
- › Battery Life: Up to 10 Years

Physical Specifications

- › Diameter: 139 mm
- › Height: 49 mm
- › Weight: 298 g
- › Colour: Matte White

Interconnection

- › Wired Interconnection: Up to 40 Devices
- › Wireless Interconnection: Up to 22 Devices
- › Wireless Frequency: 433.92 MHz
- › Wireless Range: Up to 30 metres

Installation

- › Installation Type: Indoor
- › Mounting Options: Ceiling / Wall
- › Fixing Method: Screws

Operating Environment

- › Operating Temperature: –10°C to +50°C
- › Humidity Range: <95% RH

Detection & Performance

- › Detection Type: Smoke
- › Sensor Type: Photoelectric
- › Response Time: Approx. 8 seconds
- › Alarm Volume: >85 dB @ 3m
- › Sound Pattern: ISO 8201
- › Alarm Frequency: 2400 MHz

Controls & Indicators

- › Controls: Face Push Button
- › Indicator: LED Status Indicator

Certifications & Standards

- › Product Certification: CSIRO
- › AS 3786:2014 + A1:2015 + A2:2018
- › ISO 9001:2015
- › CE EN14604:2006



To know more about our products check our website or scan the QR code.

www.watchsmokealarms.com.au

watch

