



MODEL NUMBER

W-U3000MRF

Photoelectric Smoke Alarm 240V RF Interconnected

KEY FEATURES



- ✓ Photoelectric Split Spectrum Smoke Detection
- ✓ RF Wireless Interconnection (Up to 40 Devices)
- ✓ 10-Year Integrated Lithium Backup Battery
- ✓ Hush Function
- ✓ Auto Pairing

Power & Electrical

- › Power Supply: AC Mains
- › Rated Voltage: 85–265Vac, 50Hz
- › Backup Battery: Li/MnO₂ 3V (Integrated)
- › Battery Life: 10 Years

Physical Specifications

- › Diameter: 139 mm
- › Height: 53 mm
- › Weight: 315 g
- › Colour: Matte White

Wireless Interconnection

- › Wireless Frequency: 433.92 MHz
- › Number of Devices: Up to 40
- › Operating Range: Up to 30 metres

Installation

- › Installation Type: Indoor
- › Mounting Options: Ceiling / Wall
- › Fixing Method: Screws

Operating Environment

- › Operating Temperature: –10°C to +50°C
- › Humidity Range: <95% RH

Detection & Performance

- › Detection Type: Smoke
- › Sensor Type: Photoelectric Split Spectrum
- › Response Time: Approx. 8 seconds
- › Alarm Volume: >85 dB @ 3m
- › Sound Pattern: ISO 8201
- › Alarm Frequency: 2400 MHz

Controls & Indicators

- › Controls: Test/Hush Button
- › Indicator: Dual-Colour LED Status Indicator

Certifications & Standards

- › Product Certification: CSIRO
- › AS 3786:2014 + A1:2015 + A2:2018
- › ISO 9001:2015
- › CE EN14604:2006



To know more about our products check our website or scan the QR code.

www.watchsmokealarms.com.au

watch

