



MODEL NUMBER

W-U3000BRF

Photoelectric Smoke Alarm RF Interconnected – 10 Year Battery

KEY FEATURES



- ✓ Photoelectric Split Spectrum Smoke Detection
- ✓ RF Wireless Interconnection (Up to 40 Devices)
- ✓ 10-Year Sealed Lithium Battery
- ✓ Hush Function
- ✓ Auto Pairing
- ✓ Initial Alarm Reporting (via Hushie Remote)

Power & Battery

- Power Supply: Integrated Lithium
- Li/MnO₂ Battery
- Working Voltage: 3V DC
- Battery Life: 10 Years

Physical Specifications

- Diameter: 139 mm
- Height: 38 mm
- Weight: 245 g
- Colour: Matte White

Wireless Interconnection

- Wireless Frequency: 433.92 MHz
- Number of Devices: Up to 40
- Operating Range: Up to 30 metres

Installation

- Installation Type: Indoor
- Mounting Options: Ceiling / Wall
- Fixing Method: Screws

Operating Environment

- Operating Temperature: -10°C to +50°C
- Humidity Range: <95% RH

Detection & Performance

- Detection Type: Smoke
- Sensor Type: Photoelectric Split Spectrum
- Response Time: Approx. 8 seconds
- Alarm Volume: >85 dB @ 3m
- Alarm Frequency: 2400 MHz
- Sound Pattern: ISO 8201

Controls & Indicators

- Controls: Test/Hush Button
- Indicator: Dual-Colour LED Status
- Indicator

Certifications & Standards

- Product Certification: CSIRO
- AS 3786:2014 + A1:2015 + A2:2018
- ISO 9001:2015
- CE EN14604:2006



To know more about our products check our website or scan the QR code.

www.watchsmokealarms.com.au

watch